



**Tolerances**

Shaft dia: f7 (< 55 mm id.)  
 h8 (> 55 mm id.)  
 Housing: H7

**Material: Triple-layer bushing**

Tinplated steel-layer (anti-corrosive)  
 Sintered, multiporous bronzelayer  
 PTFE sliding surface (selflubricating)

Chamfer: Inner and outer ends

This document and its contents are the exclusive property of Lagermetall AB, and may not be copied, reproduced, transmitted or communicated to a third party, or used for any purpose without written permission.

|  |  |  |                                     |                             |                                   |   |  |
|--|--|--|-------------------------------------|-----------------------------|-----------------------------------|---|--|
|  |  | General Tolerances acc to:<br><b>ISO 2768-mK</b> | File Name:<br><b>400-BM-LMB.icd</b> |                             |                                   | Template Created Date:<br><b>2016-08-16 12:46</b> |  |
|  |  |  | Drawn by:<br><b>UP</b>              | Weight g:<br><b>1330.97</b> | Material:<br><b>Triple-layers</b> |   | Drawing Created Date:<br><b>2016-09-19</b> |
| <br><a href="http://www.lagermetall.se">www.lagermetall.se</a> |  |  | <b>Wrapped bushing BM-LMB</b>       |                             |                                   | Sheet No:<br><b>1 ( 1 ) ...</b>                   | Rev.<br><b>...</b>                         |
|  |  |  |                                     |                             |                                   | Doc. No:<br><b>400-BM27080LMB</b>                 |  |