



**Tolerances**

Shaft dia: f7 (< 55 mm id.)

h8 (> 55 mm id.)

Housing: H7

**Material: Triple-layer bushing**

Copper plated steel-layer (anti-corrosive)

Sintered, multiporous bronzelayer

Acetal plastic layer (with grease pockets)

Chamfer: Inner and outer ends

This document and its contents are the exclusive property of Lagermetall AB, and may not be copied, reproduced, transmitted or communicated to a third party, or used for any purpose without written permission.

<p><b>A4</b></p> <p>ISO E</p>	<p>IRONCAD 2D drawing 3D model is available</p>	<p>General Tolerances acc to: <b>ISO 2768-mK</b></p>	<p>File Name: <b>440-POM-LMB.icd</b></p>			<p>Template Created Date: <b>2016-08-16 12:59</b></p>
			<p>Drawn by: <b>UP</b></p>	<p>Weight g: <b>72.24</b></p>	<p>Material: <b>Triple-layer</b></p>	
<p><b>LAGERMETALL</b> www.lagermetall.se</p>			<p>Wrapped triple-layer bearing with acetalplastic</p>			<p>Sheet No: <b>1 ( 1 ) ...</b></p>
						<p>Rev. <b>...</b></p>
			<p>Doc. No: <b>440-POM4045LMB</b></p>			